



---

---

## Non-silicon defoamer

### RP-6035

#### Features and advantages:

1. RP-6035 is a non-silicon antifoam agent, specially designed for light curing coating system, has extremely excellent compatibility, and has a strong defoaming, defoaming ability, does not affect the recoating property, does not have adverse interaction with the light curing system, and does not cause curtain break during episodic coating construction.
2. RP-6035 has excellent compatibility in the light curing coating system, and can be used in other thermosetting resin systems such as unsaturated polyester.
3. It has excellent recoating property and will not cause curtain break when used in the coating construction of light curing coatings.

#### Product Specifications:

appearance	Light yellow viscous liquid
Non-volatile	100%
ingredient	Non-silicon polymer

**Application:** Used in light curing coating system, unsaturated polyester system, etc.

**Recommended dosage:** For the total amount of 0.3 ~1.0%, please test the best dosage;

**Usage:** After adding, it should be mixed under a high enough shear force,  
Tianjin Ruike Chemical Co. LTD Tel:+86 18526852692  
Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin  
[tjrkhg@126.com](mailto:tjrkhg@126.com) [www.rk-chem.com](http://www.rk-chem.com)



---

and it is recommended to add before grinding.

**Packing:** 25kg iron drum.

**Storage and Precautions:** This product has not been tested or stated to be suitable for medical or food use