



---

---

## Paraffin type defoamer

### RP-6413

#### Features and advantages:

RP-6413 is a mixture of wax emulsions, mineral oils and non-ionic surfactants, suitable for scraping, spraying architectural coatings and adhesives with long-lasting results.

It has excellent continuous anti-bubble effect, and has very good compatibility, strong versatility, and can produce beautiful film. Strong combination, not easy to shrink oil, no adverse effect on the color of the paint.

#### Product Specifications:

appearance	Translucent colorless - light yellow viscous liquid
Active ingredient	100%
Specific gravity	0.86 g/ml
Ionic type	nonionic
Water solubility	Disperse in water, easily

**Applications:** Water-based coatings, water-based inks, various emulsions, water-based binders, various inorganic slurries.

#### How to use:

It can be added to the paint in the form of the original, the recommended dosage is 0.1-0.5%.

Add 50% of the mass in the grinding stage and the remaining 50% in the

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

[tjrkhg@126.com](mailto:tjrkhg@126.com)

[www.rk-chem.com](http://www.rk-chem.com)



---

---

paint mixing stage (before adding the emulsion) until the best results are achieved. Toss or shake well before use. (Layering during storage does not affect efficiency)

Below 5 ° C will be solidified or stratified, before use below 5 ° C, please use a warm bath to 30-40 ° C and fully mixed, will not affect the use efficiency.

**Packing:** 16 kg iron drum, 25 kg, 180 kg plastic drum packing.

**Storage and precautions:** no frost, below 40°C, 12 months