



---

---

## Can be recoated silk screen feel aid

### RT-3127

#### Features and advantages:

This product is a surface smooth feel agent, has increased the surface smoothness and fineness, and can be recoated screen printing to increase adhesion, the effect is remarkable, can solve the rubber paint surface screen printing, recoating problems.

1. In the two-liquid two-component elastic paint system with excellent soft feel, improve wear resistance, scratch resistance, prevent adhesion
2. Increase the scratch and wear resistance of the product in PU matte paint.
3. Improve the wear resistance of various coating products
4. Increase the surface recoating silk screen adhesion effect is **significant**

#### Product Specifications:

appearance	Transparent liquid
Active ingredient	100%
Viscosity	50-150.
ingredient	Polymer modified polydimethyloxane

#### Application field:

Rubber paint, leather paint, baking paint, ink and paint with required

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

[tjrkhg@126.com](mailto:tjrkhg@126.com)

[www.rk-chem.com](http://www.rk-chem.com)



---

---

hand feel

**Recommended dosage:** The recommended standard effective dosage is 1%, the usual dosage is about 0.5-2%, and the best dosage varies according to different formula requirements.

**How to use:** It can be directly added in the process of making paint. Or dilute with a suitable solvent to add the system, the best effect.

**Packing:** Net weight 25Kg/ barrel, 200kg/ barrel.