



Silicone wetting agent

RK-8205

Features and advantages:

It is a high performance silicone wetting agent, with ultra low surface tension, does not improve smoothness, does not affect the adhesion between layers Fastness and recoating.

1. Ultra-low surface tension (0.1% aqueous solution, static surface tension as low as 20.5mN/m)
2. Excellent substrate wettability and permeability, effectively prevent shrinkage cavity
3. Does not improve smoothness, does not affect the adhesion fastness and recoating between layers

Product specifications:

appearance	Transparent liquid
Valid copy of	100%
composition	Organosiloxane copolymer

Recommended dosage:

1. Water-based paint and ink

Recommended dosage: 0.1-1.0% for the total formula in the form of supply



2. Water fountain solution

Recommended dosage: 1.5-2.0% for the total formula in the form of supply

3. Water-based wood primer and water-based plastic paint

Recommended dosage: 0.2-0.3% of the total formula in supply form

4. Water-based leather coating or leather tanning

Recommended dosage: 0.3-0.5% of the total formula in the form of supply

5. Metallic paint

Recommended dosage: 0.3-0.5% of the total formula in the form of supply

6. Petroleum extraction, cleaning and washing products

Recommended dosage: 0.6-1.0% of the total formula in the form of supply

Usage: pre-diluted or directly added to paint in supply form.

Packing: 25KG plastic drum or 200KG iron drum.

Storage: store in unopened original packaging for 12 months from the date of production.