

## Water based wetting agent

# RK-8206

### Features and advantages:

Used for water-based wetting agent formulations, also used for solvent based wetting formulations. Good recoating is especially suitable for automotive paint wetting agent, industrial coating wetting agent, plastic coating wetting agent, building coating base material wetting agent, inkjet ink wetting agent, leather precoating primer based on polyurethane, acrylic nitro and casein emulsion system.

- 1. Suitable for water-based and solvent-based formulations
- 2. High efficiency
- 3. Good recoating

### Product specifications:

appearance	Transparent liquid
Active substance content	100%
Chemical composition	Organosiloxane copolymer

#### Recommended dosage:

 Automotive paint, industrial paint, plastic, wood and furniture paint



Recommended dosage: 0.1-1.0% for the total formula in the form of supply 2. Architectural paint Recommended dosage: 0.1-1.0% for the total formula in the form of supply 3. Decorative paint, inkjet ink Recommended dosage: 0.2-1.0% of the total formula in the form of supply 4. Leather preprimers, primers and finishes based on polyurethane, acrylic, nitro and casein systems Recommended dosage: 0.2-1.0% of the total formula in the form of supply Usage: pre-diluted or directly added to paint in supply form. Packing: 25KG plastic drum or 200KG iron drum. Storage: store in unopened original packaging for 12 months from the date of production.