

High performance defoamer

RP-6419

Features and advantages:

RP-6419 is used as a defoamer for solvent-based, solvent-free and radiation-curable coatings, especially for radiation-curable systems and two-component epoxy systems and color paint formulations. Good foam suppression effect, construction spraying foaming ability is strong, also suitable for thick coating. Application: amine/amide cured epoxy floor coatings, solvent-based and radiation cured screen printing inks, radiation cured varnish, wood and furniture coatings, amine/amide cured epoxy baking paint.

- For solvent-based, solvent-free and radiation curing formulations
- Especially suitable for color paint formula
- High efficiency
- Solvent-free

Product specification:

appearance	liquid
Effective portion	100%
Chemical composition	Organic modified polysiloxane, containing fumed silica

Application field:

Amine/amide cured epoxy floor coating

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Solvent-based and radiation-cured screen printing inks

Recommended addition

Total formula in the form of supply: 0.1-1.0

Radiation curing varnish

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Wood and furniture coatings

Recommended addition

Total formula in the form of supply: 0.1-0.8%

Amine/amide cured epoxy paint

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Leather Paint

Recommended addition

Total formula in the form of supply: 0.1-0.8%

Instructions for use:

When used for color paint formulation, it is recommended to add in the grinding stage

Stir before use

Pre-dilution with the recommended solvent will facilitate addition and mixing

Pre-dilution or directly added to the paint according to the supply form can be

Must be mixed with high shear force

Packing: 25kg plastic drum / 200kg iron drum



Storage: Store unopened original packaging without freezing and use within 12 months.